



# ITOWET Liq.

## Technical Data Sheet

### Introduction

Itowet Liq. is wetting agent in aqueous solution.for all kinds of water and oil repellent chemicals.

### 1. Features

- Itowet Liq.has surface active properties in all most all media.
- Itowet Liq. shows compatibility with cationic and nonionic textile chemicals.
- Itowet Liq. does not have any negative hydrophobic effects on
- Itowet Liq. does not have any big effects on original handle of the fiber.

### 2. Physical/Chemical Properties

<b>Appearance</b>	Liquid,
<b>pH (25 °C)</b>	3-4
<b>Ionic charge</b>	Nonionic
<b>Solubility</b>	<100g/l

### 3. Application

Itowet Liq. can applied by padding method.

#### Recommended Usage:

Padding Method:

4-10 g/l Itowet Liq (depending on the expected effect)

Drying Process:

At 130-150°C (until fabric becomes completely dry)



# ITOWET Liq.

## 4, Precautions for use

- Itowet Liq. can be stored for at least 8 months under room temperature.
- Stir well before use.
- Use under adequate ventilation is recommended. It is not safe to breathe any vapor or mist.
- Wear protective equipment when handling. Avoid direct contact with eyes and skin.
- See the Material Safety Data Sheet for further information about safe use.

This technical brochure prepared by MEKSA Company serves the purpose of providing useful information to our customers. MEKSA makes no warranties, expressed or implied, about any results. It is strongly recommended for our customers to run tests under their standard processing conditions before use.